VEHICLE PREPARATION

AREAS



- SINGLE OR DOUBLE UNITS
- CROSS DRAFT OR DOWNDRAFT
- TWO STAGE FILTRATION

Garmat® USA provides vehicle preparation areas to meet your shops' requirements. Preparation areas are designed for the removal of dust from the work area. They are capable of exhausting filtered air to the outside, or recycle the filtered air back into the shop environment. Local Fire Marshals do not permit the use of the preparation areas for spraying or priming.



VEHICLE PREPARATION AREAS

Garmat® USA Vehicle Preparation areas are constructed of e.g. steel with durable powder coated finish on facia, and ceiling panels. All units are equipped with one reverse incline fan, 5 HP motors/ single units and 10 HP motors/double units, 3 phase. Complete electrical controls are provided (including motor starter, on-off switch and pneumatic controls for recycle damper). Two stages of filtration are provided. Efficient air flow of 9,000 CFM/single units and 14,000 CFM/double units. Refer to feature table for a configuration that is appropriate for your requirements.


Note:


10100 Series = Single Units 10200 Series = Double Units


MODELS


The dimensions are exterior measurements.


MODEL	PIT	PLENUM	
10105	No	No	
10110	Yes	No	
10115	No	Yes	
10120	Yes	Yes	
10130	No	Lights & Ceiling	
10165	Yes	Yes	
10205	No	No	
10210	Yes	No	
10230	No	Lights & Ceiling	

























Garmat[®] USA reserves the right to modify or change any of the technical features mentioned in this brochure. ©2002 Garmat[®] USA

